



| Size      | Code    |
|-----------|---------|
| 2.9 Litre | RA\0003 |
| 5 Litre   | RA\0005 |
| 20 Litre  | RA\0020 |

- ✓ Biodegradable
- ✓ Non Toxic
- ✓ Non Evaporative
- ✓ Easy to Apply
- ✓ Concentrate (mix with water)
- ✓ Lubricates and protects fittings
- ✓ Low suction between panels
- ✓ Compatible with most coating systems

“We have been using Lanotec products since the job started and found that maintenance costs and downtime have been reduced considerably ”

Paul Padroth  
Caltex Refinery Project, Lytton QLD

Replaces these types of products:

Release Agent

Tilt Panel Bond Breaker

Precast Mould Oil

Lubricant for Jacks & Fittings

Rust Protection Spray

- Non staining for coloured concrete
- Does not affect polystyrene
- Safe for fibreglass, PVC, polypropylene & rubber moulds

Concrete (mix @ 1:6 parts water)

- Formwork Release Agent
- Tilt Panel Bond Breaker
- Precast Mould Oil

Scaffolding (mix @ 1:4 parts water)

- Lubricant for jacks & fittings
- Corrosion protection for tubes, jacks & fittings
- Protection of assets from concrete and paint overspray

| Container Size | Concrete @ 1:6             | Scaffolding @ 1:4 |
|----------------|----------------------------|-------------------|
| 2.9L           | 20L - *500m <sup>2</sup>   | 15L               |
| 5L             | 35L - *875m <sup>2</sup>   | 25L               |
| 20L            | 140L - *3500m <sup>2</sup> | 100L              |

\*Approximate coverage only

For MSDS, PDS & further info, please visit our website



**NATURALLY BETTER**

www.lanotec.com.au