

LANOTEC

Product Catalogue







General Purpose



Penetrant | Lubricant | Corrosion Inhibitor



-			
Size	Code	Size	Code
400g Aerosol	GP\PP-0400	10 Litre	GP\0010
750ml Spray	GP\SP-0750	20 Litre	GP\0020
5 Litre	GP\0005	200 Litre*	GP\0200
60g Aerosol	GP\PP-0060	1000 Litre*	GP\1000
*requires agitation equipment			
Empty Applicator Rottles with Label			

750ml Spray Unit | AC\SUBN-0750 | 1.5L Spray Unit | AC\SUBN-1500 | 8L Spray Unit | AC\SUBN-8000 | 18L Backpack | AC\SUBN-1800 |

EVERYDAY. EVERYTHING

- · Penetrates deep through rust, frees up rusted tools & components
- Stops squeaks for longer
- Lubricant for drilling, tapping & machining
- Cleans, rejuvenates and extends life of metal, timber, vinyl, plastic, leather, rubber, fibreglass & powder coated surfaces
- Internal storage protection of critical spares & parts
- Protection of electrical equipment & components - non conductive to 70,000 Volts
- Long lasting and resists wash off
- Prevent problems before they arise

Replaces these types of products

Penetrant

Cutting Oil

Light Lubricant

Corrosion / Rust Protector


Electrical Protectant

Silicone Spray

Rejuvenator - Leather Plastic & Vinyl

Lubricating Oil







Heavy Duty



Lubricant | Corrosion Inhibitor | Anti-Seize



Size	Code	Size	Code
400g Aerosol	HD\PP-0400	20 Litre	HD\0020
750ml Spray	HD\SP-0750	200 Litre*	HD\0200
5 Litre	HD\0005	1000 Litre*	HD\1000
10 Litre	HD\0010	*requires agitation equipment	
Empty Applicator Bottles with Label			
750ml Spray Unit	AC\SUBN-0750	1.5L Spray Unit	AC\SUBN-1500

8L Spray Unit AC\SUBN-8000 18L Backpack AC\SUBN-1800

WHEN THE GOING GETS TOUGH!

- Long lasting lubrication and protection in corrosive environments
- Non-fling high-speed & load bearing chain (x-ring & o-ring); and wire rope lubrication and protection
- Spray on anti-seize
- Marine grade protectant and lubricant
- External storage & shipping protection
- Protection of electrical equipment & components including battery terminals, boxes, connectors, outboard motors & pumps
 - non conductive to 70,000 Volts
- Cable pulling lubricant
- Extends service intervals of plant & equipment

Replaces these types of products

Marine Grade Lubricant

Anti-Seize

Tacky Lubricant

Corrosion / Rust Protectant

Chain Lube

Spray Grease

Battery Terminal Protectant

Wire Rope Spray

Viscosity

Wire Rope Lube

Lubricant | Corrosion Inhibitor



1000 Litre* HW\RL1000 *requires agitation equipment

PENETRATES + LUBRICATES + PROTECTS

- Provides long lasting lubrication and corrosion protection to wire ropes & slings
- Penetrates to the core of the rope, whilst remaining on the outer strands
- Suitable for wire ropes over 16mm or any wire ropes working in corrosive environments
- Ideal for use around waterways, coastal locations and environmentally sensitive areas (including rig, marine & portainer cranes, working in the splash zone)
- Easy to apply via spray, brush or dipping bath
- · Semi fluid formula

Replaces these types of products

Wire Rope Lube

Heavy Fluid Lubricant

Corrosion Protector








Type A Grease



Anti-seize | Lubricant | Corrosion Inhibitor







- Stops galling of stainless steel & aluminium
- Stops electrolysis due to dissimilar metal contact
- · Rubber grease and assembly lubricant
- · Non perishing to rubber (including hoses, O-rings & seals)
- Di-electric grease for multi-pin plugs (70kV)
- Protection of electrical equipment & components from moisture ingress, including multi-pin plugs and connectors
- · Drilling and cutting compound
- · Welding nozzle dip
- Wire rope lubricant (via pressure injection)

Replaces these types of products

Rubber Grease

Assembly Grease

Nickel Anti-Seize

Copper Anti-Seize

Silver Anti-Seize

Petroleum Jelly

Nozzle Dip

Wire Rope Grease

Size Code 250ml Tube GS\250T 1 Litre 235ml GS\0235 4 Litre GS\0004 200 Litre GS\0200

Viscosity









Timber Seal Timber Treatment



FOR DRESSED TIMBER

- For decking, outdoor furniture, fencing, gates, and cladding
- Penetrates into the timber, providing a natural finish
- Prevents drying, splitting, cracking & wood rot
- For weatherproofing and storage of external timber
- Can be tinted to restore colour (use oil-based tint)
- Protect metal fastenings and fittings from corrosion
- Highlights natural grain & features
- · Can be sprayed, brushed or rolled
- · Can be polished to a low sheen

Replaces these types of products

Timber Treatment

Decking Oil

Wood Preserver


Waterproofer

Coverage

Hardwood	NEW	10-15m²/L
Hardwood	OLD	8-10m²/L
Softwood	NEW	8-10m²/L
Softwood	OLD	6-8m²/L

*Approximate coverage only







Timber Seal PLUS

Timber Treatment



Size	Code
20 Litre	TS\P020
200 Litre*	TS\P200

*requires agitation equipment

FOR ROUGH SAWN TIMBER

- For boardwalks, jetties, bridges & rough sawn fence posts and railings
- Safe for environmentally sensitive areas and waterways
- Penetrates into the timber, providing a natural finish
- Prevents drying, splitting, cracking & wood rot
- For weatherproofing and storage of external timber
- Can be tinted to restore colour (use oil-based tint)
- Protect metal fastenings and fittings from corrosion
- Highlights natural grain & features
- Can be sprayed, brushed or rolled

Replaces these types of products

Timber Treatment

Wood Preserver

Waterproofer

Coverage

5-6m² per litre

Please Note

Timber Seal PLUS is too thick for domestic decking applications, and is therefore not recommended

Viscosity





Release Agent

Concrete Release Agent

FORM OIL, BOND BREAKER

Concrete (mix 1:6 parts water)

- Formwork Release Agent
- Tilt Panel Bond Breaker
- Precast Mould Oil

Scaffolding (mix 1:4 parts water)

- Lubricant for jacks & fittings
- Spatter protection for tubes, jacks & fittings
- Safe for environmentally sensitive areas and waterways
- Safe for PVC, fibreglass, polypropylene and rubber moulds. Does not affect polystyrene
- · Non staining for coloured concrete
- · Low suction between panels
- · Protection of equipment from concrete overspray

Replaces these types of products

Release Agent

Tilt Panel Bond Breaker

Precast Mould Oil

Lubricant for Jacks & Fittings

Coverage

Approx 25m² per litre of post mix (A 2.9L Release Agent mixed 1:6 with water = 500m² approx of coverage)

Please Note

Release Agent is compatible with paints and waterproof membranes. Contact Lanotec for specific information



Lano-Form

Code

RA\0003

RA\0005

RA\0020

2.9 Litre

20 Litre

Makes (mix 1:6

20 Litres

140 Litres

PREMIXED CONCRETE RELEASE AGENT

Ready to use concrete release agent

- Formwork Release Agent
- Tilt Panel Bond Breaker
- Precast Mould Oil
- Safe for environmentally sensitive areas and waterways
- Convenient when there is limited access to water for mixing concentrate
- Safe for PVC, fibreglass, polypropylene and rubber moulds. Does not affect polystyrene
- Non staining for coloured concrete
- · Low suction between panels
- Protection of equipment from concrete overspray

Concrete Release Agent

Replaces these types of products

Release Agent

Tilt Panel Bond Breaker

Precast Mould Oil

Lubricant for Jacks & Fittings

Coverage

Approx 25m² per litre

Please Note

Lano-Form is compatible with paints and waterproof membranes. Contact Lanotec for specific information













Steel Seal

Corrosion Inhibitor



Size	Code	Size	Code
750ml Spray	SS\SP-0750	20 Litre	SS\0020
5 Litre	SS\0005	200 Litre*	SS\0200
10 Litre	SS\0010	1000 Litre*	SS\1000
*requires agitation equipment			

	Empty Applicator Bottles with Label			
	750ml Spray Unit	AC\SUBN-0750	1.5L Spray Unit	AC\SUBN-1500
	8L Spray Unit	AC\SUBN-8000	18L Backpack	AC\SUBN-1800
d				

THE ULTIMATE IN CORROSION PROTECTION

- Forms a low-tack protective skin which is moisture, salt, acid and fertiliser resistant
- Stops rust dead in its tracks
- Ideal for 4WD and Light Vehicle underbodies
- For mining equipment (offshore & underground)
- For ag equipment, storage facilities and vehicles
- Component storage protection
- Corrosion protection for shipping
- · Drill pipe protection including threads and casing
- · Hermetically seals the surface
- · Skin formed is self healing

Replaces these types of products

Protective Wax

Soft Seal

Fish Oil

Corrosion / Rust Protector

Steel Preserver

Cavity Wax

Coverage

Approx 20m² per litre Only one light coat is required







Anti-Spatter

Welding Anti-Spatter | Corrosion Inhibitor



Size	Code
750ml Spray	AS\SP-0750
5 Litre	AS\0005

FOR MIG & ARC WELDING

- Can be sprayed directly onto the weld area without affecting weld integrity
- Does not contain Methylene Chloride a known carcinogen
- Can be applied in hard to reach areas reducing the need for a grinder
- Does not affect galvanising process
- Corrosion and spatter protection of welding beds, robots and spot welders
- · Can be used to protect and prolong the life of welding gloves and aprons
- Lubricant for cutting, drilling, pressing & machining
- · Short term corrosion protection

Replaces these types of products

Anti-Spatter

Cutting Fluid

Leather Glove Protector

Rust Protection Spray

Nozzle Spray

Jig Protectant



Citra-Force



Cleaner | Degreaser

POWERFUL NATURAL CLEANER\DEGREASER CONCENTRATE



Size	Code	Size	Code
400g Aerosol	CF\PP-0400	5 Litre	CF\0005
750ml Spray	CF\SP-0750	10 Litre	CF\0010
1 Litre	CF\0001	20 Litre	CF\0020
		200 Litre	CF\0200

| Empty Applicator Bottles with Label | 750ml Spray Unit | ACISUBN-0750 | 1.5L Spray Unit | ACISUBN-1500 | 8L Spray Unit | ACISUBN-8000 | 18L Backpack | ACISUBN-1800 |

 Machinery and plant cleaner, for use around workshops and wash bays

- Cleans stainless steel and aluminium without streaking
- Cleaning of electrical components and rewinds
- Designed to remove Lanotec lanolin based products
- Ideal for catering & workshop floors, pet stables, toilets, bathrooms, BBQ's, tiles & ovens
- Removes wax, tar, oil, uncured silicone, grease thread dope, bugs, fresh paint, adhesives & electrical carbon
- · Dilute with water for desired strength

Replaces these types of products

Stainless Steel Cleaner

Adhesive Remover

Quick Break Degreaser

Engine Degreaser

Pet Safe Cleaner

BBQ Cleaner

Bitumen Remover

Decarbonizing Fluid



Spray Units



- Viton™ Seals
- Stainless steel extension
- Adjustable brass nozzle with 180° rotation
- Tick box for Lanotec product identification
- Thumb lever control
- Very solid chemically resistant construction
- Translucent tank for monitoring liquid level











LANOTEC®

www.lanotec.com.au

1800 LANOTEC (1800 526 683)



Lanotec Australia Pty Ltd 87 096 795 621 PO Box 360, Archerfield QLD 4108 P: +61 7 3373 3700 F: +61 7 3373 3777

E: info@lanotec.com.au



www.youtube.com/LanotecAus



www.facebook.com/LanotecAus



www.twitter.com/Lanotec_Aus